



## RF Load / Terminators

### Salient Features

- DC~2500MHz
- Powers 50W to 100W
- Finned Termination
- High Reliability

### Applications

- In-Building System
- Outdoor Networks



RF Load / Terminators

### Technical Specifications

Part no.	JAS-RF LOAD-50 WN (M)	JAS-RF LOAD-100 WN (M)
Frequency Range	DC~2500 MHz	DC~2500 MHz
V.S.W.R	<1.2:1	<1.2:1
Impedance	50 Ohm	50 Ohm
Connector	N- Male	N- Male
Dimensions (LXBXW) mm	115 X 105 X105	160 X105 X 90
Weight	920 Grams.	1500 Grams

\*PHDCOMM company policy is one of continuing improvement, therefore we reserve the right to change the specifications without the prior notice

### Ordering Information Table

Part No.	Description
JAS-RF LOAD-50 WN (M)	Broad band (DC~2500 MHz) 50 W Terminators, with N-male connector.
JAS-RF LOAD-100 WN (M)	Broad band (DC~2500 MHz) 100 W Terminators, with N-male connector.

**For Sales Enquiry please contact:**

**PHDCOMM Private Limited**

**Corporate.Office :** 610/611, Srishti Plaza, Saki Vihar Road, Powai, Andheri-East, Mumbai-400072,

Tel: +91 22 28573050/53, Fax No:+91 22 28573051, Email: sales@phdcomm.com, Website: www.phdcomm.com